

# A101 Smart Antenna

## The Affordable All-In-One DGPS Receiver Solution



Powered by  
**Crescent**

Work smarter, not harder. The A101™ Smart Antenna offers an affordable, portable solution with professional-level accuracy for agricultural, marine, GIS mapping, and other applications.

Focus on the job at hand with fast start-up and reacquisition times, 60 cm accuracy, and an easy-to-see status indicator for power, GPS, and DGPS. The durable enclosure houses both antenna and receiver. It can be powered through various sources, making the A101 Smart Antenna ideal for a variety of applications. Dual-serial, CAN, and pulse output options make this DGPS receiver compatible with almost any interface.

### Key A101 Smart Antenna Advantages

- Affordable solution for unparalleled sub-meter performance – 60 cm accuracy, 95% of the time
- COAST™ technology maintains accurate solutions for 40 minutes or more after loss of differential signal
- Exclusive e-Dif® option where other differential signals are not practical
- Compatible with our exclusive L-Dif™ technology, for applications requiring accuracy better than 20 cm
- Fast output rates of up to 20 times per second provide the best visual guidance and automated steering signals for all types of applications
- Compact, low-profile design with fixed or magnetic mounting options is ideal for portable and dynamic applications
- Radar-simulated pulse output provides accurate ground speed

# A101 Smart Antenna

## GPS Sensor Specifications

Receiver Type:	L1 GPS	
Channels:	12 L1CA GPS	
	12 L1P GPS	
	3 SBAS or 3 additional L1CA GPS	
GPS Sensitivity	-142 dBm	
SBAS Tracking	3-channel, parallel tracking	
Update Rate:	10 Hz standard, 20Hz optional (with subscription)	
Horizontal Accuracy:	RMS(67%)	2DRMS (95%)
RTK <sup>1,2</sup>	10 mm+1 ppm	20 mm+2 ppm
SBAS (WAAS) <sup>1</sup>	0.3 m	0.6 m
Autonomous, no SA <sup>1</sup>	1.2 m	2.5 m
Pitch/Roll Accuracy	1° using tilt sensor	
Timing (1PPS)		
Accuracy:	20 ns	
Cold Start:	< 60 s typical (no almanac or RTC)	
Warm Start:	< 30 s typical (almanac and RTC)	
Hot Start:	< 10 s typical (almanac, RTC and position)	
Maximum Speed:	1,850 kph (999kts)	
Maximum Altitude	18,288 m (60,000 ft)	

## Communications

Serial Ports:	2 full-duplex RS-232, CAN
Baud Rates:	4800 - 115200
Data I/O Protocol:	NMEA 0183, NMEA 2000 <sup>3</sup> , Hemisphere GPS binary
Correction I/O Protocol:	Hemisphere GPS proprietary, RTCM v2.3 (DGPS), RTCM v3 (RTK), CMR (RTK), CMR (RTK) <sup>4</sup>
Timing Output:	1 PPS CMOS, active high, rising edge sync, 10 kΩ, 10 pF load
Event Marker Input:	CMOS, active low, falling edge sync, 10 kΩ, 10 pF load

## Environmental

Operating Temperature:	-40°C to +70°C (-40°F to +158°F)
Storage Temperature:	-40°C to +85°C (-40°F to +185°F)
Humidity:	95% non-condensing
Shock and Vibration:	Mechanical Shock: EP455 Section 5.41.1 Operational Vibration: EP455 Section 5.15.1 Random
EMC:	CE (ISO 14982 Emissions and Immunity), FCC Part 15, Subpart B, CISPR 22
Enclosure:	IP67

## Power

Input Voltage:	7 - 36 VDC with reverse polarity operation
Power Consumption:	< 3 W @ 12 VDC typical
Current Consumption:	249 mA @ 12 VDC typical
Power Isolation:	No
Reverse Polarity Protection:	Yes
Antenna Voltage:	Internal Antenna

## Mechanical

Dimensions:	10.4 H x 14.5 D (cm) 4.1 H x 5.7 D (in)
Weight:	<558 g (<19.7 oz)
Status Indicators (LED):	Power, GPS Lock
Power/Data Connector:	12-pin male (metal)
Antenna Mounting:	1-14 UNS-2A female, 5/8-11 UNC-2B adapter, and mag-mount available



Authorized Distributor:



HEMISPHERE GPS  
4110 - 9th Street S.E.  
Calgary, AB T2G 3C4  
Canada

- <sup>1</sup> Depends on multipath environment, number of satellites in view, satellite geometry, and ionospheric activity
- <sup>2</sup> Depends on baseline length
- <sup>3</sup> Requires NMEA certification
- <sup>4</sup> Receive only; does not transmit this format

Phone: 403.259.3311  
Fax: 403.259.8866  
precision@hemispheregps.com  
www.hemispheregps.com